



www.cemanco.com

951 NW 31st Avenue, Pompano Beach, FL 33069

Phone: 954-970-3099 - Fax: 954-970-3056

E-Mail: sales@cemanco.com



HT-TC041 MANUAL HYDRAULIC CUTTING TOOL

Hand operated hydraulic tool specifically designed to cut Copper, Aldrey, Aluminum, Aluminum-Steel cables, steel ropes having a max overall diameter of **1-9/16**.

The tool features a double speed action. The blades are manufactured from high strength special steel, heat treated to ensure a long service life.

The head can rotate by **90 degrees**, to enable the operator to work in the most comfortable position, and can easily be opened to allow the cutting of running cables. The **HT-TC041** features an automatic safety valve to bypass oil when reaching maximum pressure; a pressure release device can also be operated at any stage of operation.

Ideal for EHS guy wire



CEMANCO

www.cemanco.com

951 NW 31st Avenue, Pompano Beach, FL 33069

Phone: 954-970-3099 - Fax: 954-970-3056

E-Mail: sales@cemanco.com

HT-TC041

CUTTING CAPACITY			
MATERIAL	TENSILE STRENGTH (lbs./sq.in.)	MAX CUTTING DIAMETER (in)	
		HT-TC 041 TC 04 B-TC 04A	
ROPE & CONDUCTORS	COPPER	≤ 59,450	1-9/16"
	ALUMINUM	≤ 29,000	1-9/16"
	ALMELEC	≤ 49,300	1-9/16"
	STEEL	≤ 261,000	FEW INDICATIVE EXAMPLE: 7 x 0.118 = Ø out. 0.354 19 x 0.083 = Ø out. 0.413 19 x 0.091 = Ø out. 0.453
	MULTI STRANDS STEEL (STRANDS Q.TY ≥ 200)	≤ 264,000	0.709
	ACSR	≤ 261,000	1-9/16" FEW INDICATIVE EXAMPLE: 26 x 0.098 + 7 x 0.077 : Ø out. = 0.624 26 x 0.120 + 7 x 0.094 : Ø out. = 0.763 26 x 0.142 + 7 x 0.110 : Ø out. = 0.897 54 x 0.138 + 19 x 0.082 : Ø out. = 1.240 54 x 0.172 + 19 x 0.103 : Ø out. = 1.543
RODS	STEEL	≤ 87,000	0.709
		≤ 60,900	0.787
	COPPER	≤ 43,000	1.181
		≤ 36,250	1.260
	ALUMINUM	≤ 23,200	1-9/16"

Max cutting Ø in.	Dimensions in.		Weight lbs.
	length	width	
1-9/16	21.6	5.6	12.8

STORAGE

Type	Dimensions in.	Weight lbs	Supplied with the tool	Available upon request
VAL P7	28.6x8xh4.5	2.9	✳	—